



Decorative & Architectural

Technical Data Sheet

D302-STD (Rev 1/2021)

PRODUCT NAME: SUPREME GLOSS ENAMEL

Generic Type: Long Oil Modified Alkyd.

General Description:

Alkyd paint specially formulated for tropical weather to combine beauty, economy and durability. It has good fungus and mildew resistance.

Recommended Uses:

Recommended for interior and exterior use. It can be used on wood, metal and concrete surfaces that have been appropriately primed.

Features/Benefits:

- Good adhesion
- Moisture resistant
- Economical and Durable
- Provides a uniform even surface for top coating
- Anti - fungal
- East to apply
- High Gloss Finish
- Easy to Clean

Limitations of Use:

Has limited exterior durability.
Not recommended for use on floors or for immersion surface.

Technical Data

Suggested Primer:

Masonry – Kaleidoscope Alkali Sealer
Wood – Kaleidoscope Universal Undercoat
Iron and Steel – Kaleidoscope Zinc Chromate Primer. Kaleidoscope Red Oxide Zinc Chromate Primer
Aluminium, Galvanise, Zinc – Kaleidoscope Etch Primer

Product Data:

Coverage:
33 - 37 m² per 0.95 litre

Drying Time:
Touch Dry: 4 - 6 hrs
Over - coat: 16 - 18 hrs
Hard Dry: Over Night

Application:
 Brush, roller or spray.
 Thin up to 10% (370 ml) per 3.8 litres for spraying.

Gloss: High Gloss
Colour: 10 Standard colours

Thinner/Cleaner:
 Brush Kaleidoscope Thinner 2000
 Roller Kaleidoscope Thinner 2000
 Spray Kaleidoscope Thinner 2003

Flash Point:
39°C (102°F)



A Member of: kplgroup

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.tt.com • www.kscopaints.com
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

D302-STD (Rev1/2021)

PRODUCT NAME: SUPREME GLOSS ENAMEL

General Surface Preparation & Directions for Use

Ensure all areas are completely dry and free from dirt and grease. Repair cracks, nail holes and broken surfaces to obtain a smooth and uniform finish. For concrete Kaleidoscope Pol-Y-Fil can be use while for wooden surface Kaleidoscope Carpenter's Wood Filler or Kaleidoscope Pol-Y-Fil can be used.

WOODWORK (NEW):

Rub down with sand-paper and dust off. Apply one coat of Kaleidoscope Knotting Varnish to all knots, followed with one coat of Kaleidoscope Universal Undercoat and allow over night drying. Finish with two coats of Kaleidoscope Supreme Gloss Paint.

PAINTED:

Remove all loose, flaking or peeling paint to obtain a good base By scraping. Then apply one or two coats of Kaleidoscope Supreme Gloss Paint.

METAL:

Clean to hand tool finish SSPC-SP-2 or Power Tool finish SSPC-SP-3. New surface should be sand -blasted or wire- brushed to bare bright metal, then primed with one coat of Kaleidoscope Zinc Chromate Primer allowing over night drying. Finish with two coats of Kaleidoscope Supreme Gloss Paint.

PAINTED:

Previously painted surfaces should be thoroughly cleaned to remove wax, grease, dirt or flaking material. Remove grease, oil or wax with cloth moistened with mild detergent or thinner. Remove rust with Kaleidoscope Rust Converter and spot prime all bare areas as necessary. Then apply 1 or 2 coats of Kaleidoscope Supreme Gloss Paint.



A Member of:  **kplgroup**

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

D302-STD (Rev 1/2021)

PRODUCT NAME: **SUPREME GLOSS ENAMEL**

Always stir well before use. Kaleidoscope Supreme Gloss Paint may be applied by brush, roller or spray. In the latter case, the addition of 370 ml of Kaleidoscope 2000 Thinner per 3.8 litres container will be required. Always stir thoroughly before use and occasionally during use and allow over night drying between coats. When using more than one can of the same color, mix together before applying. Read all of the label prior to use.

CAUTION: Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of:  **kpl group**

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021