



Decorative & Architectural

Technical Data Sheet

D313-STD (Rev 1/2021)

PRODUCT NAME: ALUMINIUM WOOD PRIMER

Generic Type: Aluminium paste/oil modified alkyd.

General Description

Specially formulated for use as a barrier coat for sealing new wooden surfaces where resinous exudation is a likely problem.

Recommended Uses:

Specially developed as a primer/ barrier coat for sealing new wooden surfaces where resinous exudation is a likely problem.

Features/Benefits

- Good penetration into porous substrates
- Tolerant of less than optimum surface preparation
- Excellent stain resistance.
- Stops resinous exudation

Suggested Primer:
Not Required

Product Data:

No. of coats: 1

Spreading Rate (per coat):
10 - 12 m² per 0.95 litre

Drying Time:
Touch Dry: 2 – 3 hrs.
Over Coat: 12 hrs

Application:
Brush, roller or spray.
Thin up to 10% (370 ml) p. 3.785 litre for spraying.

Gloss: Matt
Colour Range: Aluminium

Thinner/Cleaner:
Brush Kaleidoscope Thinner 2000
Roller Kaleidoscope Thinner 2000
Spray Kaleidoscope Thinner 2003

Flash Point:
39°C (102°F)



A Member of: kplgroup

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

D313-STD (Rev 1/2021)

PRODUCT NAME: ALUMINIUM WOOD PRIMER

General Surface Preparation

Ensure the surface is dry and cleaned free of all dust, dirt and other debris. Rub down with abrasive paper to obtain a smooth finish.

Kaleidoscope Aluminium Wood Primer is supplied ready to apply by brush or roller. Stir well before use. Allow to dry at least 12 hours before over coating. Read label prior to use.

CAUTION: Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of:  **kplgroup**

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021