



Decorative & Architectural

Technical Data Sheet

M103-STD (Rev 1/2021)

PRODUCT NAME: DECK PAINT - Smooth & Non Skid

Generic Type: Epoxy Ester Modified Alkyd.

General Description:

A hard, tough, fast drying coating having very good abrasion resistance. Has excellent weathering properties. Very good resistance to water, sea-water, mineral oils, acids, alkalis and salts.

Recommended Uses:

For decks, gangways, steps and corridors.

Features/Benefits:

- Quick Drying
- Good resistance to water, sea water, mineral oils, acids, alkalis and salts.
- Excellent weathering properties
- Good abrasion resistance
- Durable
- Supplied smooth finish, can be non-skid with application non-skid beads (supplied seperately).

Technical Data

Suggested Primer:
Bare metal areas to be primed with Kaleidoscope Zinc Chromate Primer or Universal Metal Primer.

Solids Volume: 36%

Film Thickness (per coat):
 Wet 102 microns (4 mils.)
 Dry 36.5 microns (1 1/2 mil.)

Spreading Rate:
 7 – 9 m². @ 40microns d.f.t.

Drying Time:
 Touch Dry: 1 - 2 hrs
 Re-coat: 6 - 8 hrs
 Hard Dry: 12 hrs

Application:
 Brush, roller or spray.
 Thin 10% (370 ml) per 3.8 litre for spraying.

Gloss: Smooth - Semi Gloss
Non Skid – Matt

Colour: Green and Red

Thinner/Cleaner:
 Brush Kaleidoscope Thinner 2000
 Roller Kaleidoscope Thinner 2000



A Member of: kplgroup

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

M103-STD (Rev 1/2021)

PRODUCT NAME: **DECK PAINT - Smooth & Non Skid**

General Surface Preparation

Remove all dust, dirt, oil, grease, loose and semi-adherent paintwork, rust, mill-scale and other debris to obtain a clean dry sound surface. Clean to Hand Tool or Power Tool finish, SSPC-SP- 2 or 3, but preferably abrasive blast clean, to Brush- Off or Commercial finish, SSPC - SP-7 or 6.

Primed Areas: 2 coats.

Previously Painted: 1 or 2 coats.

Stir thoroughly before use and occasionally during use. Allow over night drying between coats.

Read labels prior to use.

CAUTION: Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of: **kplgroup**

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021