



Decorative & Architectural

Technical Data Sheet

W101-STD (Rev 1/2021)

PRODUCT NAME: N.C. SANDING SEALER

Generic Type: **Modified Nitrocellulose Sealer.**

General Description:

A very quick drying lacquer sealer having good "hold-out" and excellent "non-clogging" sanding properties, it raises wood pores to ease sanding for a smooth finish.

Recommended Uses:

An effective sealer for wooden furniture.

Features/Benefits:

- Quick Dry
- Excellent sealing
- Easy Application
- Sandable
- Available in clear and white

Limitations of Use:

Do not topcoat with gloss urethane varnish or use beneath latex type stains. Do not attempt to coat pre-waxed wood flooring. Not recommended as a finish coat for floors.

Suggested Primer:
Not Required

Product Data:

Solids Volume: 19%

Film Thickness (per coat):

Wet 125 microns (5 mils.)

Dry 25 microns (1 mil.)

No. of Coats: 1

Spreading Rate:

6.0 - 8.0 m² per 0.95 litre (US Quart)

Drying Time:

Touch Dry: 10 - 15 mins.

Overcoat: 1 hr.

Hard Dry: 1 hr.

Gloss: Glossy

Colour: Clear

Thinner/Cleaner:

Kaleidoscope Thinner 2008

Flash Point:

21°C (70°F)



A Member of: kplgroup

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

W101-STD (Rev 1/2021)

PRODUCT NAME: **N.C. SANDING SEALER**

General Surface Preparation & Directions for Use

NEW WOOD:

Sand to obtain a smooth surface, remove dust.

PREVIOUSLY COATED SURFACES:

Remove any oils, grease, polish or wax. Kaleidoscope NC Sanding Sealer should not be applied over existing finishes without first testing to determine if "lifting" would occur. For best results strip previously painted/ varnished areas to bare wood and sand to obtain a smooth surface, remove dust.

Kaleidoscope NC Sanding Sealer is supplied ready for use by brush or spray. It can be thinned with a small quantity of Kaleidoscope 2008 Thinners if desired. Apply one or two coats allowing 1 hour between applications. Overcoat with Kaleidoscope Stains, Varnishes, Lacquers, etc, as desired.

Stir thoroughly before use and occasionally during use. Read label before use.

CAUTION: Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of: **kpl group**

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021