



Decorative & Architectural

Technical Data Sheet

Z102-STD (Rev 1/2021)

PRODUCT NAME: PAINT REMOVER / STRIPPER

Generic Type: A blend of extremely strong solvents.

General Description:

Kaleidoscope Paint Remover is an effective stripper which would rapidly penetrate and lift any paint or varnish yet it will not affect the bare surface.

Recommended Uses:

For the removal of all types of paints and varnishes including epoxies, polyurethanes, stoved or baked enamels, acrylics, vinyls and other Heavy Duty High Performance coatings applied to metal.

Features/Benefits:

- Removes the toughest coatings (industrial, automotive and decorative)
- Permits safer application of thick films
- Provides for easy rinsing
- Wash off with water and allow to dry

Limitations of Use:

May cause discoloration of some types of wood. It is recommended that if wooden surface is to be clear coated, that a test area is checked for discoloration first.

Product Data:

Spreading Rate:

Dependent on thickness of coating to be removed, normally 2.5 - 5.0 m² per 0.95 litre.

Treatment Time:

5 - 15 mins (Do not allow drying out)

Cleaner:

Water

Flash Point:

Non - inflammable

Safety:

Please use rubber gloves and safety eye glasses



A Member of: kplgroup

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

Z102-STD (Rev 1/2021)

PRODUCT NAME: PAINT REMOVER / STRIPPER

General Surface Preparation

APPLICATION:

1. Use plastic or rubber gloves and goggles to protect the hands and eyes. Restrict application to an area not more than 1850 sq. cm. (approx. 2 sq. ft.) at a time.
2. Flow on a heavy coat, using a soft brush and stroking in one direction only. Allow Paint Remover to remain on surface, for 5-15 mins., until the coating is completely blistered before attempting to remove.
3. Wash surface by scraping off with scraper.
4. Further applications may be necessary with some tough coatings. Use a paint scraper/wire wool to remove the loosened coating while flushing with water. Finally abrade the surface free of all residues and allow to dry.

CAUTION: Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of: kplgroup

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021