



Decorative & Architectural

# Technical Data Sheet

D321-STD (Rev 1/2021)

## PRODUCT NAME: SCHOOLBOARD BLACK / GREEN

**Generic Type:** Long Oil Modified Alkyd.

### General Description:

Specially formulated to provide a smooth hard surface which does not "gloss-up" after repeated erasing of chalk markings.

### Recommended Uses:

For any surface where chalk will be used for marking, e.g. school boards, notice boards, etc.

### Features/Benefits:

- Low Maintenance
- Long lasting

**Suggested Primer:**  
**Not Required**

### Product Data:

**Coverage:** 7 – 9 m<sup>2</sup> per litre

### Drying Time:

**Touch Dry:** 2 - 4 hrs.

**Re-Coat:** 16 - 18 hrs.

**Hard Dry:** overnight

### Application:

Brush, roller or spray.

Thin up to 10% (370 ml) per 3.8 Litres for brushing and spraying using Kaleidoscope 2000 Thinners.

**Gloss:** Matt

**Colour:** Black

### Thinner/Cleaner:

Brush Kaleidoscope Thinner 2000

Roller Kaleidoscope Thinner 2000

Spray Kaleidoscope Thinner 2003

### Flash Point:

39°C (102°F)

**No. of Coats:** 1 or 2



A Member of: kplgroup

**Head Office** (868) 638-2213/6  
Chanka Trace, El Socorro Ext. Rd  
San Juan, Trinidad, W.I.

**South Branch** (868) 658-1818  
#99 Market Street, Marabella,  
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • [info@kplgroup.com](mailto:info@kplgroup.com) • [www.kscopaints.com](http://www.kscopaints.com)

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

# Technical Data Sheet

D321-STD (Rev 1/2021)

PRODUCT NAME: SCHOOLBOARD BLACK / GREEN

## General Surface Preparation

### NEW SURFACES WOODWORK UNPAINTED:

Rub down with sand paper and dust off. Then apply one coat of Kaleidoscope Knotting Varnish to all knots. Allow to dry then follow with two or three coats of Kaleidoscope School Board Paint. Rub down with fine abrasive paper between coats.

### WOODWORK PAINTED:

Remove all loose, flaking or peeling paint to obtain a good base. Then apply 1 or 2 coats of Kaleidoscope School Board Paint.

Allow over night drying between coats. Stir thoroughly before use and occasionally during use. Read label prior to use.

**CAUTION:** Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of: kplgroup

**Head Office** (868) 638-2213/6  
Chanka Trace, El Socorro Ext. Rd  
San Juan, Trinidad, W.I.

**South Branch** (868) 658-1818  
#99 Market Street, Marabella,  
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • [info@kplgroup.com](mailto:info@kplgroup.com) • [www.kscopaints.com](http://www.kscopaints.com)  
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021