



Decorative & Architectural

# Technical Data Sheet

D318-STD (Rev 1/2021)

## PRODUCT NAME: TEAK OIL

**Generic Type:** A Special blend of Linseed drying oils

### General Description

The low viscosity of Teak Oil achieves good penetration of bare wood surfaces to thoroughly seal and protect the surface, while enhancing the colour and beauty of the wood grain, particularly of hardwoods.

### Recommended Uses:

For treating raw bare hard woods, utilizing a simple process.

### Features/Benefits

- Excellent Penetration
- Resists cracking and peeling
- Restores the original appearance of wood
- Ensures the longevity of teak and other hardwoods

### Product Data:

**Solids Volume:** 72%

**No. of coats:** 1

**Spreading Rate:**  
7 - 15 m<sup>2</sup> per litre  
Depending on porosity

**Drying Time:**  
Overnight

**Colour:** Clear

**Gloss:** Low Sheen

**Cleaner:**  
Kaleidoscope Thinner 2000

**Flash Point:**  
39°C (102°F)



A Member of: kplgroup

**Head Office** (868) 638-2213/6  
Chanka Trace, El Socorro Ext. Rd  
San Juan, Trinidad, W.I.

**South Branch** (868) 658-1818  
#99 Market Street, Marabella,  
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • [info@kplgroup.com](mailto:info@kplgroup.com) • [www.kscopaints.com](http://www.kscopaints.com)  
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

# Technical Data Sheet

D318-STD (Rev 1/2021)

PRODUCT NAME: **TEAK OIL**

## General Surface Preparation & Directions for Use

### NEW WOOD SURFACES:

Ensure that surfaces are thoroughly dry and free from all dust, dirt and other debris. Using a dry soft cloth, apply Kaleidoscope Teak Oil fairly generously. Leave for 5-10 mins, then wipe off any excess material with a soft cloth, using a polishing motion. Finally, with a new soft cloth rub vigorously to obtain a dry burnished finish.

### PREVIOUSLY OILED SURFACES:

Every 4-6 months, repeated light applications may be required.

**CAUTION:** Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of: **kplgroup**

**Head Office** (868) 638-2213/6  
Chanka Trace, El Socorro Ext. Rd  
San Juan, Trinidad, W.I.

**South Branch** (868) 658-1818  
#99 Market Street, Marabella,  
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • [info@kplgroup.com](mailto:info@kplgroup.com) • [www.kscopaints.com](http://www.kscopaints.com)

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021