



Decorative & Architectural

# Technical Data Sheet

M106-STD (Rev 1/2021)

## PRODUCT NAME: TENNIS COURT PAINT

Generic Type: **Acrylic Latex.**

### General Description:

A quick drying tough finish having good abrasion resistance and very good weathering properties.

### Recommended Uses:

Concrete and asphalt tennis courts or other playing fields.

### Features/Benefits:

- Durable
- Excellent drying
- Good adhesion
- Good water resistance

**Suggested Primer:  
Not Required**

### Product Data:

**No. of Coats: 2**

#### Spreading Rate:

8 –10 m<sup>2</sup> per 0.95 litre depending on porosity and texture of the surface.

#### Drying Time:

Touch Dry: 20 mins.

Re-Coat: 1 hrs.

Hard Dry: 2 hr.

#### Application:

Brush, roller or spray

Thin 10% (370 m) per 3.8 litres for spraying.

**Gloss: Flat**

**Colour: Green & White**

#### Flash Point:

39°C (102°F)



A Member of: **kplgroup**

**Head Office** (868) 638-2213/6  
Chanka Trace, El Socorro Ext. Rd  
San Juan, Trinidad, W.I.

**South Branch** (868) 658-1818  
#99 Market Street, Marabella,  
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • [info@kplgroup.com](mailto:info@kplgroup.com) • [www.kscopaints.com](http://www.kscopaints.com)  
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

# Technical Data Sheet

M106-STD (Rev 1/2021)

PRODUCT NAME: TENNIS COURT PAINT

## General Surface Preparation & Directions for Use

### NEW WOOD SURFACES:

Ensure that surfaces are thoroughly dry and free from all dust, dirt, grease and grime. Very smooth concrete surfaces should be etched with a dilute solution of Muriatic Acid and allowed to dry thoroughly. Apply two full coats of Kaleidoscope Tennis Court Paint.

### PREVIOUSLY PAINTED SURFACES:

Remove all wax and polish, grease and grime. Remove all flaking paint, sand to a smooth surface. Ensure that surface is free from all dust. Apply one or two coats of Kaleidoscope Tennis Court Paint as necessary.

Kaleidoscope Tennis Court Paint is supplied ready to apply by brush or roller. Stir well before use. Allow to dry at least 2 hours between coats. Read label prior to use.

**CAUTION:** Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of: kplgroup

**Head Office** (868) 638-2213/6  
Chanka Trace, El Socorro Ext. Rd  
San Juan, Trinidad, W.I.

**South Branch** (868) 658-1818  
#99 Market Street, Marabella,  
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • [info@kplgroup.com](mailto:info@kplgroup.com) • [www.kscopaints.com](http://www.kscopaints.com)  
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021