

# Technical Data Sheet

Decorative & Architectural

D212-STD (Rev 1/2021)

# PRODUCT NAME: TEXTURED COATING

# Generic Type: Acrylic Co-polymer Emulsion.

## General Description:

A heavy bodied, hard wearing textured coating capable of filling minor cracks, crevices and small holes. Also is able to obscure the unsightly appearance of poor quality workmanship on surfaces. Has good exterior durability and fungus resistance. Provides a decorative finish.

### **Recommended Uses:**

Suitable as an attractive decorative textured finish for masonry and wooden surfaces. Also useful for obliterating unsightly appearance of poorly finished surfaces.

## Features/Benefits:

- Excellent resistance to mildew and fungus
- Excellent opacity
- Hard, tough, abrasive resistant
- Various Patterns with various rollers
- Long life and decorative appeal
- Available in Fine 1.0-1.5mm and Coarse 2.0-2.5mm
- Exterior or interior use

#### **Suggested Primer:**

Concrete/cement: – No primer New Wood – Kaleidoscope Universal Undercoat Metal – Kaleidoscope Metal Primer, Red Oxide or Zinc Chromate

It should be noted that texture coating can be applied directly onto the surface eliminating the need for priming



## **Product Data:**

#### No. of Coats: 1

#### **Spreading Rate:**

1.2 - 1.5 m<sup>2</sup> per 0.95 litre
13 - 16 ft<sup>2</sup> per 0.95 litre depending on porosity and texture of the surface and film thickness applied.

#### Setting and Drying Time:

Depends on porosity and texture of surface, relative humidity and ambient temperature.

Initial "Set" 3 - 5 mins. Final "Set" 10 - 15 mins. Hard Dry: Over night

#### **Application:**

Large stippling brush, texture roller or medium naplambswool roller (\*available for purchase).

Gloss: Flat

Colour: White and Off White

Cleaner: Water

Flash Point: Not applicable

 Head Office
 (868) 638-2213/6
 South Branch
 (868) 658-1818

 Chanka Trace, El Socorro Ext. Rd
 #99 Market Street, Marabella,

 San Juan, Trinidad, W.I.
 Trinidad, W.I.

 ©2021 Kaleidoscope Paints Ltd • info@kplgrouptt.com • www.kscopaints.com

 ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

D212-STD (Rev 1/2021) PRODUCT NAME: TEXTURED COATING

# **General Surface Preparation & Directions for Use**

Clean the surface free of all dust, dirt, oil, grease, moss, algae and other debris. Also remove any loose, flaking, peeling and semi-adherent paint by hand scraping, wire-brushing and abrasive sanding to obtain a clean, firm, sound surface.

# **TREATMENT FOR ALGAE AND FUNGUS INFECTION:**

Use water to wash affected areas thoroughly. Dilute 1 part Domestic Bleach with 1 part water and apply liberally, using brush or sponge. Follow with 1 coat Kaleidoscope Sterilizing Solution and allow drying overnight.

Dry porous surfaces should be moderately soaked with clean water before application. Use a large stippling brush to quickly apply an even coat of adequate thickness. At initial "set," use roller to achieve the desired effect.

When final "set" is occurring, use flattening sheet \* to flatten sharp points, peaks and edges to prevent a hazardous abrasive surface.

\* Fabricate a firm flat board / sheet 15 - 30cm. (6 - 12 ins.) wide by 25 - 40 cm. (10 - 15 ins.) long using plywood or aluminium sheet.

**CAUTION:** Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.** 



 Head Office
 (868) 638-2213/6
 South Branch
 (868) 658-1818

 Chanka Trace, El Socorro Ext. Rd
 #99 Market Street, Marabella,

 San Juan, Trinidad, W.I.
 Trinidad, W.I.

 ©2021 Kaleidoscope Paints Ltd • info@kplgrouptt.com • www.kscopaints.com

 ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021