



Decorative & Architectural

Technical Data Sheet

D213-STD (Rev 1/2021)

PRODUCT NAME: TROWEL - TEXCOAT

Generic Type: Styrene Acrylic Emulsion Resin.

General Description:

A heavy bodied, hard wearing trowel-texcoat capable of filling minor cracks, crevices and small holes. Also is able to obscure the unsightly appearance of poor quality workmanship on surfaces. Has good exterior/interior durability and fungus resistance. Provides a decorative wall finish.

Recommended Uses:

Concrete, Block and Brickwork, Solid Plaster, Fibre Cement, Wallboards, Monolithic Building Systems.

Features/Benefits:

- Excellent resistance to mildew and fungus
- Hard, tough, abrasive resistant
- Weatherproofs and waterproofs
- Long life and decorative appeal
- Hides imperfection in Masonry and Wood surfaces
- Available in: Fine 1.0-1.5mm
Coarse 2.0-2.5mm
- Interior and exterior use

Suggested Primer:

Concrete/cement: – No primer necessary.

Product Data:

No. of Coats: 1

Available: in 3 Grades Fine, Medium, Coarse

Coverage (per coat):

1.25 - 1.50 sq.ft. per litre depending on porosity and texture of the surface and film thickness applied, grade used.

Setting and Drying Time:

Depends on porosity and texture of surface, relative humidity and ambient temperature.

Initial Set: 15 - 20 mins Final Set: 1 hr
Hard Dry: Over night

Application:

Trowel in a swirling motion with flat trowel. (See directions for use).

Gloss: Flat

Colour: White (White, Off White Pastel Colours available by special minimum order of 50 Gallons)

Cleaner: Water

Flash Point: Not applicable



A Member of: kplgroup

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

D213-STD (Rev 1/2021)

PRODUCT NAME: **TROWEL - TEXCOAT**

General Surface Preparation

Clean the surface free of all dust, dirt, oil, grease, moss, algae and other debris. Also remove any loose, flaking, peeling and semi-adherent paint by hand scraping, wire-brushing and abrasive sanding to obtain a clean, firm, sound surface.

TREATMENT FOR ALGAE AND FUNGUS INFECTION:

Use water to wash affected areas thoroughly. Dilute 1 part Domestic Bleach with 1 part water and apply liberally, using brush or sponge. Wash surface free of bleach and allow to dry. Follow with 1 coat Kaleidoscope Sterilising Solution and allow to dry overnight.

Directions for Use

Apply a thin even coat of Trowel-Texcoat to a small area with a trowel (as if plastering the surface) allow to set for 15-20 Mins, then using a plastic ceiling float or wooden float, work the material in a circular motion to achieve the textured pattern. Return excess material to pail.

Trowel-Texcoat is supplied in a consistency ready for use and should need no thinning. mix thoroughly before use and thin sparingly with water only if necessary to ease application.

CAUTION: Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of: **kplgroup**

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com
ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021