



Decorative & Architectural

Technical Data Sheet

W104-STD (Rev 1/2021)

PRODUCT NAME: NC LACQUER SATIN

Generic Type: Modified Nitrocellulose with Matting Agent.

General Description:

Kaleidoscope NC Lacquer Satin is an economical, fast drying Satin Finish, formulated to bring out the richness of wood grains in furniture.

Recommended Uses:

A high quality satin gloss finishing coat for quality wooden furniture, doors, cupboards, etc.

Features/Benefits:

- Satin finish
- Easy to repair damage
- Fast drying
- Economical
- Excellent flow and leveling

Suggested Primer:
Not Required

Product Data:

Solids Volume: 24.5%

Film Thickness (per coat):

Wet 37.5 microns (1.5 mils.)

Dry 9 microns (0.37 mil.)

No. of Coats: 1

Spreading Rate:

6.0 - 8.0 m² per 0.95 litres

Drying Time:

Touch Dry: 5 mins.

Overcoat: 1 hr.

Hard Dry: 1 hr.

Gloss: Satin

Colour: Clear

Thinner/Cleaner:

Kaleidoscope Thinner 2008

Flash Point:

21°C (70°F)



A Member of: kplgroup

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021



Decorative & Architectural

Technical Data Sheet

W104-STD (Rev 1/2021)

PRODUCT NAME: **NC LACQUER SATIN**

General Surface Preparation & Directions for Use

NEW WOODEN SURFACES:

Rub down with fine sand paper and dust off all loose powdery material. Ensure that the surface is dry and cleaned of all dirt, dust, oil grease and other debris. Seal all knots with Kaleidoscope Knotting Varnish. Fill all nail holes, cracks, crevices with Kaleidoscope Carpenter's Wood Filler or Kaleidoscope Pol-Y-Fil. Then apply one coat of Kaleidoscope N.C Sanding Sealer by brush, roller or spray and rub down with fine abrasive paper to obtain a sound firm smooth surface. Follow with one or two coats of Kaleidoscope NC Lacquer Satin.

PREVIOUSLY VARNISHED:

If not in sound condition, strip with Kaleidoscope Paint Remover and treat as **"NEW"**. Rub down existing lacquer thoroughly; fill any cracks, crevices, holes with Kaleidoscope Carpenter's filler or Kaleidoscope Pol-Y-Fil. Then apply one coat Kaleidoscope NC Sanding Sealer and rub down with fine abrasive paper to obtain a sound firm smooth surface. Follow with one or two coats of Kaleidoscope NC Lacquer Satin.

Stir thoroughly before use and occasionally during use, allowing 1 hour drying time between coats. Read label prior to use.

CAUTION: Use only with adequate ventilation. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an approved particulate respirator (Follow respirator manufacturer's direction for respirator use) or leave the area. **Avoid contact with eyes.** Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. **If swallowed, get medical attention immediately.**



A Member of:  **kplgroup**

Head Office (868) 638-2213/6
Chanka Trace, El Socorro Ext. Rd
San Juan, Trinidad, W.I.

South Branch (868) 658-1818
#99 Market Street, Marabella,
Trinidad, W.I.

©2021 Kaleidoscope Paints Ltd • info@kplgroup.com • www.kscopaints.com

ISO 9001 DOC Control #KPL-QD-19/REV 01-1 TDS Revision #1/2021